

CAM-IP3155W-PV-28-AI

5MP Active Deterrence Full Color Fixed Lens IP Turret



FEATURES

- 5MP, H.265, 24x7 full color
- 2.8 Fixed Lens
- 0.002Lux@F1.0
- Smart Illumination
- Built-in Microphone
- Face Detection
- License Plate Detection
- True WDR, 3DNR
- Micro SD up to 256G
- IP67, PoE, white

Specifications

Video	
Imaging Device	1/2"
Effective Pixels	5MP 2880 (H) x1620 (V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.002lux @ F1.0(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	2.8mm
Max. Aperture Ratio	F No. 1.0
Angular Field of View	Horizontal:110°, Vertical:58°, Diagonal: 132°
Min. Object Distance	2m
Lens Type	Fixed(M12)
Operational	
IR LED	1
WarmLight	2
IR Viewable Length	Up to 30m
WarmLight Viewable Length	Up to 30m
Type of complementary light	Default warm light, switchable infrared light
Red Blue Light	2 (1 Red&1 Blue)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Image Setting	Full Color Mode/Day&Night Mode/Schedule

White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	Built-in microphone&Speaker
Hardware Reset	Yes
Smart Feature	PID,LCD,PD/VD,SOD,CC,CD,QD,Heat MAP,RSD,LPD,FD (detection)
Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Mainstream@30fps 5MP(2880x1620),4MP(2592x1520) 3MP(2304x1296),1080P(1920x1080) 720P(1280x720) Substeam@30fps 720P(1280x720),VGA(640x480),QVGA(320x240) Mobilestream@30fps VGA(640x480), QVGA (320x240)
Video Quality Ajustment	256Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
IP	IPv6
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
Application Programming Interface	ONVIF(Profile S/G/T)
Web Viewer	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Environmental	
Operating Conditions	-30 ~ +60°C/less than ≤ 95% RH
Ingress Protection	IP67
Electrical	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Mechanical	
Material	Metal
Dimensions (HxWxD)	100*100*90mm
Weight	425g